

8Ω Stereo Power - 4X1300W

4Ω Stereo Power - 4X2600W

2Ω Stereo Power - 4X3380W

GISEN DSP series is the digital amplifier with DSP and network port. It can be controlled by PC software. And its parameters can be adjusted in distant, as well as multiple amplifiers can be on-line controlled at the same time by network connection. Each channel has independent limiter and compressor, all parameters can be adjusted. Applied to situations like KTV, Performance , club, business conference, entertainment club, etc.

Hum&Noise: -112dB

Channelseparation(Crosstalk): >70dB(1kHz)

Damping Factor 1kHz,8ohms: >1000

Frequency Response: 20Hz-34KHz, +0/-0.3dB, 1W/8Ω

Input Impedance (balanced) : 20KΩ

USB connector: controlling paraments by PC software

Internet input connector: long-range control by connectingamplifier and internet

Internet output connector: multiple amplifiers on-line controlby connecting to the internet input ofthe next amplifier

Cooling: front-to-rear airfl ow, temperature controlled speed

Amplifier protection: short circuit, open circuit, directvoltage, high temperature, radio-frequency, ultralowfrequenc, current peak limitery.

Dimensions (H*W*L): 88x488x438mm

Carton Dimension (H*W*L): 155x600x550mm

Power Requirement: 180V-240VAC(90V-120VAC), 50-60Hz

Net Weight: 13.5kg

Gross Weight: 16.5kg